

STANDARDS PRESENTATION
TO
CALIFORNIA OCCUPATIONAL SAFETY AND HEALTH STANDARDS BOARD

Attachment No. 1

Page 1 of 3

PROPOSED STATE STANDARD,
TITLE 8, CHAPTER 4

Amend Section 3465 to read:

§ 3465. Terminal Facilities.

(a) The structural integrity of docks, piers, wharves, terminals and working surfaces shall be maintained.

(1) Dockboards (car and bridge plates) shall be designed, constructed, and maintained to prevent vehicles from running off the edge.

* * * * *

Note: Authority cited: Section 142.3, Labor Code. Reference: Section 142.3, Labor Code.

**STANDARDS PRESENTATION
TO
CALIFORNIA OCCUPATIONAL SAFETY AND HEALTH STANDARDS BOARD**

Attachment No. 1

Page 2 of 3

PROPOSED STATE STANDARD,
TITLE 8, CHAPTER 4

Amend Section 3472 to read:

§ 3472. Cranes and Other Hoisting Equipment.

* * * * *

(k) A seat (lap) belt, meeting the requirements of 49 CFR 571.208-210 for a Type 1 seat belt assembly, shall be installed on the operator's seat of high speed container gantry cranes where the seat trolleys.

* * * * *

Note: Authority cited: Section 142.3, Labor Code. Reference: Section 142.3, Labor Code.

**STANDARDS PRESENTATION
TO
CALIFORNIA OCCUPATIONAL SAFETY AND HEALTH STANDARDS BOARD**

Attachment No. 1

Page 3 of 3

PROPOSED STATE STANDARD,
TITLE 8, CHAPTER 4

Amend Section 3475 to read:

§ 3475. Vehicles

* * * * *

(g) A distance of not less than 20 feet (~~4.56.1~~m) shall be maintained between the first two vehicles in a check-in, check-out, roadability, or vessel loading/discharging line. This distance shall be maintained between any subsequent vehicles behind which employees are required to work.

* * * * *

Note: Authority cited: Section 142.3, Labor Code. Reference: Section 142.3, Labor Code.